

ALLEN-CURBFOX-CF 5000

KERB LAYING SLIPFORMER



Concrete Screw Feeder Conveyor increases safety of operating crew.



COMPACT—SAFE—SIMPLE

ALLEN-CURBFOX-CF 5000



**Concrete Screw Feeder
TM discharge at steep angle
promotes easy slide of
concrete in the chute
without need for additional
labour to pull the Concrete.**

SPECIFICATIONS OF ALLEN-CURBFOX-CF 5000

1)	DIMENSIONS	Length: 3.6m Width: 2.5m Height: 2m
2)	POWER	Engine Model : 3445TCIGMCZ Engine Rating 40hp @ 1500 rpm. Number of Cylinders: 3 Nos. Type of Cooling: Water Cooled (WC) Aspiration: Turbocharge Aftercooler
3)	TRACTION	All wheel drive insures operation in almost any grade condition. Tires: 57cm diameter with 'V' tread provide high
4)	CONTROLS	Precise electronic sensors and controls. Sensors: Front, Rear, Slope Sensors. Steering Feedback Sensor.
5)	HYDRAULICS	Main & Drive Pumps. Cylinders for elevation, slope & steering.
6)	CAPABILITIES	Cub and Gutter upto 55 cm in height & 60cm wide in offset position.
7)	CAPACITIES	Hydraulic reservoir : 110 litres. Fuel: 157 liter.
8)	FEEDER CONVEYOR	OPTIONALCONCRETE FEEDER SCREW CONVEYOR complete with Hydraulic Drive, hopper & discharge chute.
(Note: We reserve the right to make any design improvement and changes in actual supply)		

**ALB ALLEN BUILDWELL
PRIVATE LIMITED**

Mumbai Sales Office: B 206, Arjun Centre,
Govandi (E), Mumbai-88. India.
Landline: 022 -25569044, 25513030
Web Site: www.allenbuildwell.com
Email: info@allenbuildwell.com;
sales@allenbuildwell.com
Mumbai Sales: 8422892959